

Mobile Printer



PORTI-S30/S40




Technical Specification

Item	Specification
Printing	Direct thermal printing
Paper loading	Easy paper loading (CLAMSHELL design)
Characters per line	40cpl
Character size	English : 9 ×24dots, 12 ×24dots Korean : 16 ×24dots [24 ×24dots]
Dots available	384dots
Resolution	203dpi, 8dots/mm
Print width	2-inch (48mm, 384dots)
Printing speed	50mm/sec
Weight	250g
Interfaces	RS-232C [TTL] , IrDA Ver. 1.0 [Bluetooth]
Paper supplied	Thermal roll paper, label roll (57mm wide, 30mm or 40mm φ)
Barcode supported	PDF417 (2-dimension), Code39, Code93, Code128, UPC, EAN, KAN, JAN, CODABAR,ITF
Dimensions (W ×D ×H)	75 ×103 ×34mm
Battery	Rechargeable 7.4V / 1.2A (Li-ion)
Battery duration	1 hour continuous printing
Battery charger	Input (100~250VAC 50~60Hz), Output (8.6V / 0.8A), 4 hours full charge time
Print head duration	50Km

※ The appearance and specification of the product would be changed without notice in order to improve it. The production may be a little bit different from the real situation.

General Features

- Pocket Size (75 ×103 ×34mm)
- Light weight (250g)
- Very silent printing thru direct thermal printing method
- High speed (50mm/sec)
- High resolution (203dpi:8dots/mm)
- RS-232C[TTL] and IrDA Ver. 1.0[Bluetooth]
- Easier maintenance with self-diagnostics
- Microsoft windows CE/98/ME/2000 OS compatible



Application

Retail, Transportation, Warehousing & Distribution, Point of sales, point of Transaction, Hospitality, Gaming, Healthcare, Traveling and Mobile computing

Standard Accessories

Battery charger, Roll paper, RS-232C[TTL] interface cable, Carrying leather case