

## PORTI-SD40 – 2" Portable Pocket Printer



### General Features

- Pocket Size (97mm x 109mm x 44.7mm).
- Lightweight (350g).
- Impact Dot Matrix Printing.
- Uni-directional printing.
- RS-232 or TTL and Bluetooth Interfaces for maximum flexibility.
- Easy paper loading (clamshell design)
- Easy maintenance with self diagnostics
- Microsoft Windows 98/ME/XP/2000 compatible.
- Battery indicator.
- Text and graphic printing.
- Re-Chargeable batteries

### Technical Specification

Printing	Serial Impact Dot Matrix
Paper Loading	Clamshell Design
Number of Columns per line	40 (4x8 font)
Print Feed Pitch	3.52mm (10 dot lines)
Print Width	46.8mm (180 dots/line)
Printing Speed	1.8 line/sec ± 20%
Inking	Ink ribbon cartridge (Citizen IR-91)
Print Mechanism	Citizen MD-911
Dimensions (W x D x H)	97mm x 109mm x 44.7mm
Weight	350g (including battery + paper roll)
Paper Supplied	57.5mm wide (40 mm Ø) (Ordinary paper or pressure sensitive)
Interface	Bluetooth and RS-232C or TTL
Battery	Re-chargeable 7.4VDC/1100mAh (Li-ion) 1 hour continuous printing
Battery Charger	Input 100 to 240VAC, 50 to 60Hz, Output 8.4VDC (800ma), 4 hrs full charge time
Print Head Life	1.0 million lines
Relative Humidity	30 to 80% (non-condensing)
Operating temperature	0°C to 40°C

### Standard Accessories

Battery Charger, Roll of Paper, Serial interface cable.